

# CV20AQ

Automotive Computer Vision SoC

## Key Features

### Computer Vision Engine

- Convolutional neural network (CNN)- / deep neural network (DNN)-based processing to enable detection, classification, tracking, and more
- Dense optical flow engine
- Tools for high- and low-level algorithm development
- CNN toolkit for easy porting with Caffe, PyTorch, TensorFlow, and ONNX

### Stereo Processing Engine

- Enabling generic obstacle detection, terrain modeling, and more

### Advanced Image Processing


- Multi-exposure line-interleaved high dynamic range (HDR)
- Real time multi-scale / multi-field of view (FoV) generation
- Hardware dewarping engine support
- Multiple camera support
- Superior low-light processing
- RGGB / RCCB / RCCC / RGB-IR / monochrome sensor support

### High-Efficiency Video Encoding

- 8MP30 H.264 video encoding performance
- Flexible multi-streaming capability
- Multiple constant bit rate (CBR) and variable bit rate (VBR) control modes
- Smart H.264 encoder algorithms

### Target Applications

- Single- / multi-camera advanced driver assistance systems (ADAS)
- Driver monitoring systems (DMS) and in-cabin solutions
- Single- / multi-channel electronic mirrors with blind spot detection (BSD)
- Parking assistance systems




## Overview

Ambarella's CV20AQ offers high-performance and power-efficient computer vision acceleration, superior image processing (ISP), and H.264 video compression in a single system on chip (SoC). Ambarella's highly efficient CVflow<sup>®</sup> computer vision engine delivers DNN processing and a dedicated stereo vision accelerator to enable efficient implementation of stereo algorithms for the next generation of intelligent automotive cameras.

Ambarella's ISP provides outstanding imaging in low-light conditions while its high dynamic range (HDR) processing extracts maximum image detail in high-contrast scenes, enhancing the computer vision capabilities of the chip while delivering crisp video for driver viewing. CV20AQ delivers high-resolution video recording and streaming at very low bit rates with efficient encoding in H.264 video format. It includes a suite of advanced cybersecurity features such as secure boot with TrustZone<sup>®</sup> and secure memory, true random number generator (TRNG), one-time programmable memory (OTP), DRAM scrambling and virtualization, and a programmable secure level for each peripheral interface.

Fabricated in advanced 10 nm process technology, the CV20AQ achieves an industry-leading combination of high performance and low power for computer vision applications. It is an ideal platform for implementing single- and multi-camera ADAS, DMS and in-cabin solutions, single- and multi-channel electronic mirrors with BSD, and intelligent parking assistance systems.



# General Specifications

## Processor Cores

- Quad-core Arm®Cortex®-A53 up to 1 GHz
  - 32 KB / 32 KB L1 cache, 1 MB L2 cache
- Arm Cortex-R52 456 MHz
  - 32 KB / 32 KB I/D L1 cache, 1 MB of embedded SRAMs
- NEON™ SIMD and FPU acceleration
- AES / SHA1 / SHA2-256 crypto acceleration using Arm V8 extensions

## Computer Vision Processor

- CVflow processor optimized for high-performance CNN / DNN execution
- Disparity mapping
- Dense optical flow engine

## Video Input

- Multi-sensor input with independent image signal processor (ISP) configuration
- Three MIPI CSI-2® ports (one port with virtual channels)

## Video Output

- Two MIPI CSI-2 / MIPI DSI® ports
- On-screen display (OSD) engine and overlays

## CMOS Sensor / Image Processing

- Processing up to 480 MPixel/s
- Lens shading, fixed-pattern noise correction
- Multi-exposure HDR (line-interleaved sensors)

- 3D motion-compensated temporal filtering (MCTF)
- RGGB / RCCB / RCCC / RGB-IR / monochrome sensor support
- Adjustable auto exposure (AE) / auto white balance (AWB)
- Dynamic range (WDR and HDR) engine
- Chromatic aberration correction
- Geometric distortion correction
- Gamma compensation and color enhancement
- Vignetting compensation
- 3-axis electronic image stabilization (EIS)
- Crop, mirror, flip, 90° / 270° rotation

## Video Encoding

- H.264 MP / HP L5.0
- 8MP30 maximum encoding performance
- Flexible group of pictures (GOP) configuration with I and P frames
- Multiple CBR and VBR control modules

## Security Features

- Secure boot with TrustZone®, TRNG, OTP, DRAM scrambling and virtualization

## Tools for Development

- CNN toolkit to ease the porting of CNNs trained using frameworks such as Caffe, TensorFlow, or ONNX
- Compiler, debugger, and profiler for both Arm and microcode development

## Memory Interfaces

- LPDDR4x / LPDDR4 up to 1.8 GHz clock rate, 32-bit data bus for data, up to 4 GB capacity
- Two SD controllers
- Boot from SPI / SPI NAND with BCH / SPI NOR / USB / eMMC
- Single- / dual- / quad- / octal-SPI NOR and single- / dual- / quad-SPI NAND

## Peripheral Interfaces

- Six CAN FD controllers
- Two Ethernet ports with data transfer rates of 10- / 100- / 1000-Mbps
- One USB 2.0 port configurable as device / host with PHY
- Multiple SSI / SPI, IDC, and UART
- Multiple GPIO ports, PWM, steppers, ADC
- Watchdog timer, general purpose timers, and JTAG
- Audio interface (I²S)

## Physical

- 10 nm low power complimentary metal-oxide semiconductor (CMOS)
- FC TFBGA package (14x14 mm, 0.65 mm pitch)
- Operating temperature -40°C to +125°C (T<sub>j</sub>)
- Automotive qualified (AEC-Q100 Grade-2)

# CV20AQ Camera Development Platform

The CV20AQ camera development platform contains the necessary tools, software, hardware, and documentation to develop a camera utilizing the powerful CVflow processor while supporting development of customized features.

## Evaluation Kit (EVK)

- CV20AQ main board with connectors for sensor / lens board and peripherals
- Sensor board: Sony, onsemi, Omnivision, and others
- Datasheet, BOM, schematics, and layout
- SDK and reference application with C source code available with additional licensing

## Software Development Kit (SDK)

- ISO 26262-compliant SDK, OS, and middleware
- Royalty-free libraries for ISP, dewarp, and video recording
- Image tuning and manufacturing calibration tools
- Safety documentation for applications required to meet ISO 26262 standards
- Detailed documentation including a programmer's guide and more
- CNN / DNN training, profiling, and porting tools

[www.ambarella.com/contact-us/](http://www.ambarella.com/contact-us/)

Copyright Ambarella International LP. All rights reserved. Ambarella and the Ambarella logo are trademarks of Ambarella International LP. All other brands, product names, and company names are trademarks of their respective owners. The information in this document is believed to be reliable, but may project preliminary functionality not yet available. Ambarella makes no guarantee or warranty concerning the accuracy and availability of said information and shall not be responsible for any loss or damage whatever nature resulting from the use of, or reliance upon it. Ambarella does not guarantee that the use of any information contained herein will not infringe upon patent, trademark, copyright, or other rights of third parties. Ambarella reserves the right to make changes in the product and /or its specifications presented in this publication at any time without notice.